

**NIJ  
0101.06  
CERTIFIED**



**Country of Certification:** USA  
**Ballistic Standard:** NIJ 0101.06  
**NIJ Model:** UG062XG  
**Threat Level:** II  
**Areal Density:** 0.96 lb/ft<sup>2</sup>  
**Thickness:** 0.24"  
**Composition:** Kevlar® Comfort XLT™ / Goldflex® Hybrid  
**Stitching:** 1"x1" Diamond Quilt in Woven Fabric, Shoulder Box and Waist Tack  
**Ballistic Package:** 70 denier Ripstop Cover  
 Nylon Urethane Backed  
 Heat Sealed Seams  
 Patented Internal Desiccant  
**Ply Count:** 28  
**NIJ 0101.06 Size Range:** C1 to C5

### BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1768 fps.	.357 Mag New V50	1669 fps.
9mm Conditioned V50	1737 fps.	.357 Mag Conditioned V50	1684 fps.
9mm BFS	32.5 mm	.357 Mag BFS	36.7 mm
9mm New RPI	1841.7	.357 Mag New RPI	1738.5
9mm Conditioned RPI	1809.4	.357 Mag Conditioned RPI	1754.2

**SPECIAL THREAT TESTED: 9MM 127GR SXT AND 357 SIG 125GR GDHP**

### OPTIONAL EXTERNAL CARRIERS



Extra  
Concealable  
Carrier  
(CC)



Tactical  
Outer  
Carrier  
(TOC)



Tactical  
Response  
Carrier  
(TRC)



Uniform  
Shirt Carrier  
(USC)



Clean Front  
Carrier  
(CFC)



Quilted Outer  
Carrier  
(QOC)