



# NIJ 06 LEVEL IIIA - UG3AKXP

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

**THREAT  
LEVEL  
IIIA**

**NIJ  
0101.06  
CERTIFIED**



<b>Country of Certification:</b>	USA
<b>Ballistic Standard:</b>	NIJ 0101.06
<b>NIJ Model:</b>	UG3AKXP
<b>Threat Level:</b>	IIIA
<b>Areal Density:</b>	1.26 lb/ft <sup>2</sup>
<b>Thinness:</b>	0.28"
<b>Composition:</b>	Kevlar® Comfort XLT™ / Kevlar® XP™ Hybrid
<b>Stitching:</b>	1"x1" Diamond Quilt in Woven Fabric, Shoulder Box and Waist Tack
<b>Ballistic Package:</b>	200 denier Ripstop Cover Nylon Urethane Backed Heat Sealed Seams Patented Internal Desiccant
<b>Ply Count:</b>	25
<b>NIJ 0101.06 Size Range:</b>	C1 to C5

## BALLISTIC PERFORMANCE AT CERTIFICATION

.357 Sig New V50	1914 fps.	.44 Mag New V50	1725 fps.
.357 Sig Conditioned V50	1890 fps.	.44 Mag Conditioned V50	1743 fps.
.357 Sig BFS	27.0 mm	.44 Mag BFS	36.4 mm
.357 Sig New RPI	1519.0	.44 Mag New RPI	1369.0
.357 Sig Conditioned RPI	1500.0	.44 Mag Conditioned RPI	1383.3

**SPECIAL THREAT TESTED: 9MM 127GR SXT AND 357 SIG 125GR GDHP**

## OPTIONAL EXTERNAL CARRIERS



Extra  
Concealable  
Carrier  
(CC)



Tactical  
Outer  
Carrier  
(TOC)



Tactical  
Response  
Carrier  
(TRC)



Uniform  
Shirt Carrier  
(USC)



Clean Front  
Carrier  
(CFC)



Quilted Outer  
Carrier  
(QOC)

PO Box 280 | 1 Sentry Drive | Dover, TN 37058  
TOLL FREE (866) 920-5940 | FAX (866) 920-5941

[www.gharmorsystems.com](http://www.gharmorsystems.com)



**READY IS THE ONLY OPTION.**